

The pdfcolfoot package

Heiko Oberdiek
<heiko.oberdiek at gmail.com>

2007/09/09 v1.1

Abstract

Since version 1.40 pdfTeX supports several color stacks. This package uses a separate color stack for footnotes that can break across pages.

Contents

1	User interface	1
1.1	Other packages or classes	2
2	Interface for package or class writers	2
2.1	Macro <code>\pdfcolfoot@switch</code>	2
2.2	Macro <code>\pdfcolfoot@current</code>	2
3	Implementation	2
3.1	Identification	2
3.2	Load package <code>pdfcol</code>	3
3.3	Color stack for footnotes	3
3.4	Patch <code>\@makefntext</code>	3
3.5	Patch <code>\@makecol</code>	3
4	Test	5
5	Installation	6
5.1	Download	6
5.2	Bundle installation	6
5.3	Package installation	6
5.4	Refresh file name databases	7
5.5	Some details for the interested	7
6	References	7
7	History	7
	[2007/01/08 v1.0]	7
	[2007/09/09 v1.1]	8
8	Index	8

1 User interface

Just load the package:

```
\usepackage{pdfcolfoot}
```

The package assigns a color stack for footnotes and patches the appropriate internal macros to support this color stack.

1.1 Other packages or classes

This package `pdfcolfoot` redefines `\@makecol` and `\@makefnctext`. This can cause conflicts if other packages or classes also change these macro in an incompatible way. Sometimes it can help to change the package order.

2 Interface for package or class writers

Two macros `\pdfcolfoot@switch` and `\pdfcolfoot@current` need to be added to get support of the color stack for footnotes. This package `pdfcolfoot` already patches many macros to add these two macros. If a package or class that deals with `\@makefnctext` or `\@makecol` is not recognized by this package, the package/class author can add these two macros in his package/class.

2.1 Macro `\pdfcolfoot@switch`

Color commands inside footnotes should use the special color stack for footnotes. Macro `\pdfcolfoot@switch` sets this special color stack. (It can be called several times). But caution, footnotes for minipages should not be affected. This package patches `\@makefnctext` for this purpose.

2.2 Macro `\pdfcolfoot@current`

In \LaTeX the footnote stuff goes into box `\footins` that is placed on the page (`\@makecol`). Two things need consideration:

- The footnote area should not interfere with the normal color stack. Macro `\normalcolor` inside a group helps it stores the current color of the normal stack and restores it after the group.
- If a footnote is broken across a page boundary, we need the latest color of the footnote area in the previous page. This is set by macro `\pdfcolfoot@current`.

As example the changes for `\@makecol` are shown (however this macro is already patched by this package):

```
\gdef\@makcol{%
...
\setbox\@outputbox\vbox{% or similar
...
\color@begingroup
\normalcolor
\footnoterule % using normal color (black)
\csname pdfcolfoot@current\endcsname
\unvbox\footins
\color@endgroup
}%
...
}
```

We use `\csname` to call macro `\pdfcolfoot@current`. If package `pdfcolfoot` is not loaded, `\pdfcolfoot@current` is not defined. In this case `\csname` defines the undefined macro with meaning `\relax` and we do not get an error because of undefined command.

3 Implementation

3.1 Identification

```

1 (*package)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{pdfcolfoot}%
4 [2007/09/09 v1.1 pdfTeX's color stack for footnotes (HO)]%

```

3.2 Load package pdfcol

```

5 \RequirePackage{pdfcol}[2007/09/09]
6 \ifpdfcolAvailable
7 \else
8 \PackageInfo{pdfcolfoot}{%
9 Loading aborted, because color stacks are not available%
10 }%
11 \expandafter\endinput
12 \fi

```

3.3 Color stack for footnotes

Version 1.0 has used `\current@color` as initial color stack value, since version 1.1 package pdfcol with its default setting is used.

```

13 \pdfcolInitStack{foot}

```

3.4 Patch \@makefnctext

`\pdfcolfoot@switch` Macro `\pdfcolfoot@switch` switches the color stack. Subsequent color calls uses the color stack for footnotes.

```

14 \newcommand*{\pdfcolfoot@switch}{%
15 \pdfcolSwitchStack{foot}%
16 }

17 \AtBeginDocument{%
18 \newcommand*{\pdfcolfoot@makefnctext}{}%
19 \let\pdfcolfoot@makefnctext\@makefnctext
20 \renewcommand{\@makefnctext}[1]{%
21 \pdfcolfoot@makefnctext{%
22 \if@minipage
23 \else
24 \pdfcolfoot@switch
25 \fi
26 #1%
27 }%
28 }%
29 }

```

3.5 Patch \@makecol

`\pdfcolfoot@current` When the footnote area starts, the color should continue with the latest color value of the previous footnote area. This color is available on the current top of the color stack.

```

30 \newcommand*{\pdfcolfoot@current}{%
31 \pdfcolSetCurrent{foot}%
32 }

```

For convenience we use `\detokenize` for patching `\@makecol` and related macros.

```

33 \begingroup\expandafter\expandafter\expandafter\endgroup
34 \expandafter\ifx\csname detokenize\endcsname\relax
35 \PackageWarningNoLine{pdfcolfoot}{%
36 Missing e-TeX for patching \string\@makecol
37 }%
38 \expandafter\endinput
39 \fi

```

```

40 \newif\ifPCF@result
41 \def\pdfcolfoot@patch#1{%
42   \ifx#1\@undefined
43   \else
44     \ifx#1\relax
45     \else
46       \begingroup
47         \toks@{%
48           \let\on@line\@empty
49           \expandafter\PCF@CheckPatched
50           \detokenize\expandafter{#1pdfcolfoot@current}\@nil
51         \ifPCF@result
52           \PackageInfo{pdfcolfoot}{\string#1\space is already patched}%
53         \else
54           \expandafter\PCF@CanPatch
55           \detokenize\expandafter{%
56             #1\setbox\@outputbox\vbox{\footnoterule}%
57           }%
58           \@nil
59         \ifPCF@result
60           \PackageInfo{pdfcolfoot}{\string#1 is being patched}%
61           \expandafter\PCF@PatchA#1\PCF@nil#1%
62         \else
63           \PackageInfo{pdfcolfoot}{%
64             \string#1\space cannot be patched%
65           }%
66         \fi
67       \fi
68     \expandafter\endgroup
69     \the\toks@
70   \fi
71 \fi
72 }
73 \expandafter\def\expandafter\PCF@CheckPatched
74   \expandafter#\expandafter1\detokenize{pdfcolfoot@current}#2\@nil{%
75   \ifx\#2\%
76     \PCF@resultfalse
77   \else
78     \PCF@resulttrue
79   \fi
80 }
81 \edef\PCF@BraceLeft{\string{}}
82 \edef\PCF@BraceRight{\string{}}
83 \begingroup
84   \edef\x{\endgroup
85     \def\noexpand\PCF@CanPatch
86       #1\detokenize{\setbox\@outputbox\vbox}\PCF@BraceLeft
87       #2\detokenize{\footnoterule}##3\PCF@BraceRight
88     }%
89   \x#4\@nil{%
90     \ifx\#2#3#4\%
91       \PCF@resultfalse
92     \else
93       \PCF@resulttrue
94     \fi
95 }
96 \def\PCF@PatchA#1\setbox\@outputbox\vbox#2#3\PCF@nil#4{%
97   \PCF@PatchB{#1}#2\PCF@nil{#3}#4%
98 }
99 \def\PCF@PatchB#1#2\footnoterule#3\PCF@nil#4#5{%
100   \toks@{%
101     \def#5{%

```

```

102     #1%
103     \setbox\@outputbox\vbox{%
104         #2%
105         \footnoterule
106         \pdfcolfoot@current
107         #3%
108     }%
109     #4%
110 }%
111 }%
112 }
113 \def\pdfcolfoot@all#1{%
114     \begingroup
115     \let\on@line\@empty
116     \PackageInfo{pdfcolfoot}{%
117         Patching \string\@makecol\space macros (#1)%
118     }%
119     \endgroup

```

LaTeX base macro:

```

120 \pdfcolfoot@patch\@makecol

```

Class aastex:

```

121 \pdfcolfoot@patch\@makecol@pplt

```

Class memoir:

```

122 \pdfcolfoot@patch\mem@makecol
123 \pdfcolfoot@patch\mem@makecolbf

```

Class revtex4:

```

124 \pdfcolfoot@patch\@combineinserts

```

Package changebar:

```

125 \pdfcolfoot@patch\ltx@makecol

```

Package dblfnote:

```

126 \pdfcolfoot@patch\dfn@latex@makecol

```

Package fancyhdr:

```

127 \pdfcolfoot@patch\latex@makecol

```

Package lscape:

```

128 \pdfcolfoot@patch\LS@makecol

```

Package lineno:

```

129 \pdfcolfoot@patch\LN@orig@makecol

```

Package stfloats:

```

130 \pdfcolfoot@patch\org@makecol
131 \pdfcolfoot@patch\fn@makecol

```

```

132 }
133 \AtBeginDocument{\pdfcolfoot@all{AtBeginDocument}}
134 \pdfcolfoot@all{AtEndOfPackage}
135 \endpackage

```

4 Test

```

136 \test1
137 \NeedsTeXFormat{LaTeX2e}
138 \AtEndDocument{%
139     \typeout{}%
140     \typeout{*****}%
141     \typeout{*** \space Check the PDF file manually! \space ***}%
142     \typeout{*****}%
143     \typeout{}%

```

```

144 }
145 \begingroup\expandafter\expandafter\expandafter\endgroup
146 \expandafter\ifx\csname pdfcompresslevel\endcsname\relax
147 \else
148   \pdfcompresslevel=0 %
149 \fi
150 \documentclass[12pt,a5paper]{article}
151 \usepackage{pdfcolfoot}[2007/09/09]
152 \dimen\footins=\baselineskip % for testing
153 \begin{document}
154   Black\footnote{Black \textcolor{blue}{Blue}\Blue} Black} %
155   \textcolor{red}{Red\newpage Red} Black%
156 \end{document}
157 </test1>

```

5 Installation

5.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/pdfcolfoot.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcolfoot.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

5.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

5.3 Package installation

Unpacking. The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex pdfcolfoot.dtx
```

¹<http://ftp.ctan.org/tex-archive/>

[2007/09/09 v1.1]

- Use of package pdfcol.
- Test file added.

8 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	M
<code>\@LN@orig@makecol</code> 129	<code>\mem@makecol</code> 122
<code>\@combineinserts</code> 124	<code>\mem@makecolbf</code> 123
<code>\@empty</code> 48, 115	
<code>\@makecol</code> 36, 117, 120	
<code>\@makecol@popt</code> 121	
<code>\@makefntext</code> 19, 20	
<code>\@nil</code> 50, 58, 74, 89	
<code>\@outputbox</code> 56, 86, 96, 103	
<code>\@undefined</code> 42	
<code>\@</code> 75, 90, 154	
A	
<code>\AtBeginDocument</code> 17, 133	
<code>\AtEndDocument</code> 138	
B	
<code>\baselineskip</code> 152	
<code>\begin</code> 153	
C	
<code>\csname</code> 34, 146	
D	
<code>\detokenize</code> 50, 55, 74, 86, 87	
<code>\dfn@latex@makecol</code> 126	
<code>\dimen</code> 152	
<code>\documentclass</code> 150	
E	
<code>\end</code> 156	
<code>\endcsname</code> 34, 146	
<code>\endinput</code> 11, 38	
F	
<code>\fn@makecol</code> 131	
<code>\footins</code> 152	
<code>\footnote</code> 154	
<code>\footnoterule</code> 56, 87, 99, 105	
I	
<code>\if@minipage</code> 22	
<code>\ifPCF@result</code> 40, 51, 59	
<code>\ifpdfcolAvailable</code> 6	
<code>\ifx</code> 34, 42, 44, 75, 90, 146	
L	
<code>\latex@makecol</code> 127	
<code>\LS@makecol</code> 128	
<code>\ltr@makecol</code> 125	
	N
	<code>\NeedsTeXFormat</code> 2, 137
	<code>\newcommand</code> 14, 18, 30
	<code>\newif</code> 40
	<code>\newpage</code> 155
	O
	<code>\on@line</code> 48, 115
	<code>\org@makecol</code> 130
	P
	<code>\PackageInfo</code> 8, 52, 60, 63, 116
	<code>\PackageWarningNoLine</code> 35
	<code>\PCF@BraceLeft</code> 81, 86
	<code>\PCF@BraceRight</code> 82, 87
	<code>\PCF@CanPatch</code> 54, 85
	<code>\PCF@CheckPatched</code> 49, 73
	<code>\PCF@nil</code> 61, 96, 97, 99
	<code>\PCF@PatchA</code> 61, 96
	<code>\PCF@PatchB</code> 97, 99
	<code>\PCF@resultfalse</code> 76, 91
	<code>\PCF@resulttrue</code> 78, 93
	<code>\pdfcolfoot@all</code> 113, 133, 134
	<code>\pdfcolfoot@current</code> 30, 106
	<code>\pdfcolfoot@makefntext</code> ... 18, 19, 21
	<code>\pdfcolfoot@patch</code>
	... 41, 120, 121, 122, 123, 124,
	125, 126, 127, 128, 129, 130, 131
	<code>\pdfcolfoot@switch</code> 14, 24
	<code>\pdfcolInitStack</code> 13
	<code>\pdfcolSetCurrent</code> 31
	<code>\pdfcolSwitchStack</code> 15
	<code>\pdfcompresslevel</code> 148
	<code>\ProvidesPackage</code> 3
	R
	<code>\renewcommand</code> 20
	<code>\RequirePackage</code> 5
	S
	<code>\setbox</code> 56, 86, 96, 103
	<code>\space</code> 52, 64, 117, 141
	T
	<code>\textcolor</code> 154, 155
	<code>\the</code> 69
	<code>\toks@</code> 47, 69, 100
	<code>\typeout</code> 139, 140, 141, 142, 143

	U		X
<code>\usepackage</code>	151	<code>\x</code> 84, 89
	V		
<code>\vbox</code>	56, 86, 96, 103	