

The `hypcap` package

Heiko Oberdiek
<heiko.oberdiek at googlemail.com>

2008/09/08 v1.10

Abstract

This package tries a solution of the problem with hyperref, that links to floats points below the caption and not at the beginning of the float. Therefore this package divides the task into two part, the link setting with \capstart or automatically at the beginning of a float and the rest in the \caption command.

Contents

1 Usage	2
1.1 Package options	2
1.2 User commands	2
1.3 Limitations	3
2 Implementation	3
3 Installation	5
3.1 Download	5
3.2 Bundle installation	5
3.3 Package installation	6
3.4 Refresh file name databases	6
3.5 Some details for the interested	6
4 History	7
[1999/02/13 v1.0]	7
[2000/08/14 v1.1]	7
[2000/09/07 v1.2]	7
[2001/08/27 v1.3]	7
[2001/09/06 v1.4]	7
[2006/02/20 v1.5]	7
[2007/02/19 v1.6]	7
[2007/04/09 v1.7]	7
[2008/04/14 v1.8]	7
[2008/08/11 v1.9]	7
[2008/09/08 v1.10]	7
5 Index	8

1 Usage

The package `hypcap` requires that `hyperref` is loaded first:

```
\usepackage[...]{hyperref}  
\usepackage[...]{hypcap}
```

1.1 Package options

The names of the four float environments `figure`, `figure*`, `table`, or `table*` can be used as option. Then the package redefines the environment in order to insert `\capstart` (see below) in the beginning of the environment automatically.

Option `all` enables the redefinitions of all four float environments. For other environments see the user command `\hypcaprefdef`.

1.2 User commands

`\capstart` **`\capstart`:** First this command increments the counter (`\@capttype`). Then it makes an anchor for package `hyperref`. At last `\caption` is redefined to remove the anchor setting part from `hyperref`'s `\caption`.

The package expects the following structure of a float environment:

```
\begin{float}...  
\capstart  
...  
\caption{...}  
...  
\end{float}
```

There can be several `\caption` commands. For these you need `\capstart` again:

```
\capstart ... \caption... \capstart ... \caption...
```

And the `\caption` command itself can be put in a group.

With the options, described above, the extra writing of `\capstart` can be avoided. Consequently, there must be a `\caption` in every environment of this type, specified by the option. If you want to use more than one `\caption` in this environment, you have to state `\capstart` again.

`\hypcapspace` **`\hypcapspace`:** Because it looks poor, if the link points exactly at top of the figure, there is additional space: `\hypcapspace`, the default is `0.5\baselineskip`, examples:

```
\renewcommand{\hypcapspace}{0pt} removes the space  
\renewcommand{\hypcapspace}{1pt} sets a fix value
```

`\hypcaprefdef` **`\hypcaprefdef`:** If there are other float environments, that should automatically execute `\capstart`, then a redefinition with `\hypcaprefdef` can be tried:

```
\hypcaprefdef{myfloat}
```

Only environments with one optional parameter are supported.

`\capstartfalse` **`\capstartfalse, \capstarttrue`:** Since 2008/09/08 v1.10.
`\capstartrue` They disable and enable `\capstart`. They can be used to cancel the effect of a redefined float environment. Example:

```

\documentclass{article}
\usepackage{hyperref}
\usepackage[figure]{hypcap} [2008/09/08]

\begin{document}
\section{Hello World}
\begin{figure}
\caption{Figure with caption A}
\end{figure}
\capstartfalse
\begin{figure}
Figure without caption
\end{figure}
\capstarttrue
\begin{figure}
\caption{Figure with caption B}
\end{figure}
\end{document}

```

1.3 Limitations

- Packages that redefine \caption or \@caption.

2 Implementation

1 (*package)

Package identification.

2 \NeedsTeXFormat{LaTeX2e}
 3 \ProvidesPackage{hypcap} %
 4 [2008/09/08 v1.10 Adjusting anchors of captions (HO)]

For unique command names this package uses hc@ as prefix for internal command names.

First we check, if package hyperref is loaded:

5 \@ifundefined{hyper@@anchor}{%
 6 \PackageError{hypcap}{You have to load 'hyperref' first}\@ehc
 7 \endinput
 8 }{}

\hc@org@caption Save the original meaning of \caption:

9 \newcommand*\hc@org@caption{}
 10 \let\hc@org@caption\caption

\if@capstart The switch \if@capstart helps to detect \capstart commands with missing \caption macros. Because \caption can occur inside a group, assignments to the switch have to be made global.

11 \newif\if@capstart

\hypcapspace The anchor is raised by \hypcapspace.

12 \newcommand*\hypcapspace{.5\baselineskip}

\ifcapstart

13 \newif\ifcapstart
 14 \capstarttrue

\capstart The macro \capstart contains the first part of the \caption command: Incrementing the counter and setting the anchor.

15 \newcommand*\capstart{%
 16 \ifcapstart
 17 \H@refstepcounter\@capttype % first part of caption
 18 \hyper@makecurrent\@capttype}

	<pre> 19 \global\let\hc@currentHref\@currentHref 20 \vspace*{-\hypcapspace}% 21 \begingroup 22 \let\leavevmode\relax 23 \hyper@anchor\@currentHref\relax 24 \endgroup 25 \vspace*{\hypcapspace}% 26 \hc@hyperref{\let\caption\hc@caption}% 27 \global\@capstarttrue 28 \global\advance\csname c@\@capttype\endcsname\@ne 29 \fi 30 } </pre>
	<pre> 31 \@ifpackagelater{hyperref}{2007/04/09}{% 32 \let\hc@hyperref\@gobble 33 }{% 34 \let\hc@hyperref\@firstofone 35 } </pre>
\hc@caption	The new \caption command without the first part is defined in the macro \hc@caption. <pre> 36 \def\hc@caption{% 37 \global\advance\csname c@\@capttype\endcsname\@ne 38 \@dblarg{\hc@caption\@capttype}% 39 } </pre>
\hc@@caption	This is a copy of package hyperref's \@caption macro without making the anchor, because this is already done in \capstart. <pre> 40 \long\def\hc@@caption#1[#2]#3{% 41 \let\caption\hc@org@caption 42 \global\@capstartfalse 43 \ifHy@hypertexnames 44 \hyper@makecurrent\@capttype 45 \else 46 \global\let\@currentHref\hc@currentHref 47 \fi 48 \par\addcontentsline{% 49 \csname ext@\#1\endcsname}{#1}{% 50 \protect\numberline{% 51 \csname the\#1\endcsname 52 }{\ignorespaces #2}% 53 }% 54 \begingroup 55 \parboxrestore 56 \normalsize 57 \makecaption{\csname fnum@\#1\endcsname}{% 58 \ignorespaces#3% 59 }% 60 \par 61 \endgroup 62 } </pre>
\hypcapredef	The macro \hypcapredef prepares the call of \hc@redef that will redefine the environment that is given in the argument. <pre> 63 \def\hypcapredef#1{% 64 \expandafter\hc@redef\csname hc@org#1\expandafter\endcsname 65 \csname hc@orgend#1\expandafter\endcsname 66 \expandafter{\#1}% 67 } </pre>
\hc@redef	The old meaning of the environment is saved. Then \capstart is appended in the begin part. The end part contains a check that produces an error message in case of \capstart without \capstart (\capstart has incremented the counter).

```

68 \def\hc@redef#1#2#3{%
69   \newcommand#1{}%
70   \expandafter\let\expandafter#1\csname#3\endcsname
71   \expandafter\let\expandafter#2\csname end#3\endcsname
72   \renewenvironment*{#3}[1][]{%
73     \ifx\\#1\\%
74       #1\relax
75     \else
76       #1[##1]% hash-ok (compatibility for float)
77     \fi
78     \capstart
79   }{%
80   \if@capstart
81     \PackageError{hypcap}{You have forgotten to use \string\caption}%
82     \global\@capstartfalse
83   \else
84   \fi
85   #2%
86 }%
87 }

```

At last the options are defined and processed.

```

88 \DeclareOption{figure}{\hypcapredef{\CurrentOption}}
89 \DeclareOption{figure*}{\hypcapredef{\CurrentOption}}
90 \DeclareOption{table}{\hypcapredef{\CurrentOption}}
91 \DeclareOption{table*}{\hypcapredef{\CurrentOption}}
92 \DeclareOption{all}{%
93   \hypcapredef{figure}%
94   \hypcapredef{figure*}%
95   \hypcapredef{table}%
96   \hypcapredef{table*}%
97 }
98 \ProcessOptions\relax
99 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

<CTAN:macros/latex/contrib/oberdiek/hypcap.dtx> The source file.

<CTAN:macros/latex/contrib/oberdiek/hypcap.pdf> Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

<CTAN:install/macros/latex/contrib/oberdiek.tds.zip>

TDS refers to the standard “A Directory Structure for T_EX Files” (<CTAN:tds/tds.pdf>). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

¹<ftp://ftp.ctan.org/tex-archive/>

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex hypcap.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
hypcap.sty → tex/latex/oberdiek/hypcap.sty
hypcap.pdf → doc/latex/oberdiek/hypcap.pdf
hypcap.dtx → source/latex/oberdiek/hypcap.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your T_EX distribution (teT_EX, mikT_EX, ...) relies on file name databases, you must refresh these. For example, teT_EX users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk hypcap.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hypcap.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex hypcap.dtx
makeindex -s gind.ist hypcap.idx
pdflatex hypcap.dtx
makeindex -s gind.ist hypcap.idx
pdflatex hypcap.dtx
```

4 History

[1999/02/13 v1.0]

- A beginning version, published in newsgroup `comp.text.tex`:
“Re: `hyperref` and `figures`”²

[2000/08/14 v1.1]

- Global assignments of `\if@capstart` in order to allow `\caption` in groups.
- Option `all` added.

[2000/09/07 v1.2]

- Package in dtx format.

[2001/08/27 v1.3]

- Bug fix with hyperref’s pdfmark driver
(`\leavevmode` in `\hyper@anchor/\pdf@rect`).

[2001/09/06 v1.4]

- Small fixes in the dtx file.

[2006/02/20 v1.5]

- Code is not changed.
- New DTX framework.

[2007/02/19 v1.6]

- Fix for hypertexnames=false.

[2007/04/09 v1.7]

- Stuff in `\caption` moved to `hyperref`. This avoids redefinitions of `\caption` and `\@caption` (idea of Axel Sommerfeldt).
- Fix for subfigure (Marco Kuhlmann, Amilcar do Carmo Lucas).

[2008/04/14 v1.8]

- `\hc@redef` fixed to get package `float` work (Axel Sommerfeldt).

[2008/08/11 v1.9]

- Code is not changed.
- URLs updated.

[2008/09/08 v1.10]

- `\capstartfalse` and `\capstarttrue` added.

²Url: <http://groups.google.com/group/comp.text.tex/msg/5c9b47b001a9379c>

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols \@capstartfalse 42, 82 \@capstarttrue 27 \@capttype 17, 18, 28, 37, 38, 44 \@currentHref 19, 23, 46 \@dblarg 38 \@ehc 6 \@firstofone 34 \@gobble 32 \@ifpackagelater 31 \@ifundefined 5 \@makecaption 57 \@ne 37 \@parboxrestore 55 \\ 73	\hc@currentHref 19, 46 \hc@hyperref 26, 32, 34 \hc@org@caption 9, 41 \hc@redef 64, 68 \hypcapedef 2, 63, 88, 89, 90, 91, 93, 94, 95, 96 \hypcapspace 2, 12, 20, 25 \hyper@anchor 23 \hyper@makecurrent 18, 44 A \addcontentsline 48 \advance 28, 37	I \if@capstart 11, 11, 80 \ifcapstart 13, 16 \ifHy@hypertexnames 43 \ifx 73 \ignorespaces 52, 58
		L
		\leavevmode 22
B \baselineskip 12	M \m@ne 28	
		N
C \capstart 2, 15, 78 \capstartfalse 2 \capstarttrue 2, 14 \caption 10, 26, 41, 81 \csname 28, 37, 49, 51, 57, 64, 65, 70, 71 \CurrentOption 88, 89, 90, 91	\NeedsTeXFormat 2 \newcommand 9, 12, 15, 69 \newif 11, 13 \normalsize 56 \numberline 50	P \PackageError 6, 81 \par 48, 60 \ProcessOptions 98 \protect 50 \ProvidesPackage 3
		R
D \DeclareOption 88, 89, 90, 91, 92	\renewenvironment 72	
		V
E \endcsname 28, 37, 49, 51, 57, 64, 65, 70, 71 \endinput 7	\vspace 20, 25	
H \H@refstepcounter 17 \hc@caption 38, 40 \hc@caption 26, 36		