

The `hypdoc` package

Heiko Oberdiek
<heiko.oberdiek at googlemail.com>

2010/02/03 v1.8

Abstract

This package adds hyper features to the package `doc` that is used in the documentation system of L^AT_EX 2 _{ε} . Bookmarks are added and references are linked as far as possible.

Contents

1 Features	2
2 Usage	2
2.1 Options	3
2.2 Simple example	3
2.3 Example <code>source2e.tex</code>	3
3 Implementation	4
3.1 Options	4
3.2 Package loading	4
3.2.1 Patch for bug latex/4096	5
3.3 Bookmarks	5
3.4 <code>\tableofcontents</code>	6
3.5 <code>\listoffigures</code>	6
3.6 <code>\listoftables</code>	7
3.7 <code>\thebibliography</code>	7
3.8 <code>\theindex</code>	7
3.9 <code>\theglossary</code>	8
3.10 Index	9
3.11 <code>\PrintDescribeMacro</code>	11
3.12 <code>\PrintMacroName</code>	11
3.13 <code>\theCodelineNo</code>	12
3.14 <code>\SpecialUsageIndex</code>	12
3.15 <code>\autoindex</code>	12
3.16 <code>\SpecialEnvIndex</code>	13
3.17 <code>\SortIndex</code>	13
3.18 <code>\@rglossary</code>	13
3.19 <code>\MacroIndent</code>	14
4 Installation	14
4.1 Download	14
4.2 Bundle installation	14
4.3 Package installation	14
4.4 Refresh file name databases	15
4.5 Some details for the interested	15

5 History	15
[2002/05/10 v1.0]	15
[2006/02/20 v1.1]	16
[2006/04/27 v1.2]	16
[2006/06/01 v1.3]	16
[2006/06/02 v1.4]	16
[2007/04/11 v1.5]	16
[2007/11/12 v1.6]	16
[2009/12/10 v1.7]	16
[2010/02/03 v1.8]	16
6 Index	16

1 Features

The package adds the following features:

Bookmarks: For supporting bookmarks package `hyperref` is loaded. Some `TeX` code inside section titles can cause problems during bookmark processing; these can be warnings, ugly bookmark titles or even errors. With the help of `\pdfstringdefDisableCommands` or `\texorpdfstring` you can manage these things, see `hyperref`'s package documentation.

Additional bookmarks: Unnumbered bookmark entries are generated for:

- Table of contents
- List of figures
- List of tables
- Index
- Glossary

Option `numbered` controls, whether these section or chapters should be numbered. The exception is the table of contents if this it would be the first numbered section. Then just a bookmark is added.

Metadata: The loaded package `hyperref`, enforced by option `pdffusitle`, tries to detect `\title` and `\author` and sets the corresponding PDF information fields. In case of problems see the previous item about bookmarks. These entries can be overwritten or new ones added by `\hypersetup` after the packages is loaded, see documentation of package `hyperref`.

References, links: Because of package `\hyperref` `\ref` become links, also `\url`, footnote referencing are supported.

Index: The main part of this package deals with index links in order to support the kind of index that package `doc` provides.

Thumbnails: Package `thumbpdf` is loaded for the case that the PDF file also should contain thumbnails, see the documentation of this package. But thumbnail embedding is not really necessary, because nowadays Acrobat Reader is able to generate and view thumbnails on the fly.

2 Usage

The purpose of this packages is to add PDF features to the documentation of `LaTeX` packages. Thus just load the package in the driver file that generates the documentation:

```
\usepackage{hypdoc}
```

Package `doc` is loaded by `hypdoc`, thus you also can replace a `\usepackage{doc}` with this line. At any case, the package must be loaded before macros of package `doc` such as `\CodelineIndex` or `\PageIndex` are used.

If the class `ltxdoc` is used, you can also use the configuration file for this class to add package `hypdoc`. Add the following line to the file `ltxdoc.cfg` (or create a new one):

```
\AtEndOfClass{\RequirePackage{hypdoc}}
```

2.1 Options

There is one option `numbered`. It controls, whether the starred versions of section or chapter inside `\tableofcontents`, `\listoffigures`, ... should be replaced by the non-star versions.

2.2 Simple example

Example of a simple driver file `foobar.drv` of a package `foobar`. Often the driver file is packed in the file `foobar.dtx` and can be extracted by `docstrip` or if an instruction file for `docstrip` is provided by:

```
tex foobar.ins
```

Note that although `docstrip` doesn't rely on L^AT_EX, sometimes you need to run the `.ins` file through L^AT_EX. Oddly enough, often the only L^AT_EX feature in use is `\NeedsTeXFormat{LaTeX2e}` in the first line.

```
\documentclass{ltxdoc}
\usepackage{hypdoc}
\RecordChanges
\EnableCrossrefs
\CodelineIndex
\begin{document}
\title{Title for package \texttt{foobar}}
\author{Author of package \texttt{foobar}}
\date{...}
\maketitle
\tableofcontents
\DocInput{foobar.dtx}
\PrintChanges
\PrintIndex
\end{document}
```

Then compile it, for example with pdfL^AT_EX.

```
pdflatex foobar.drv
makeindex -s gind.ist foobar.idx
makeindex -s gglo.ist -o foobar.gls foobar.glo
pdflatex foobar.drv
```

You will need several cycles until the cross references and similar things are correct.

2.3 Example source2e.tex

The source code of the base of L^AT_EX is available as a bunch of `.dtx` files. L^AT_EX provides the file `source2e.tex` to merge them all together.

Now you can either load package `hypdoc` in a private copy of this file (please, respect the LPPL) or use the configuration file `ltxdoc.cfg`. Example that also sets A4 paper size:

```
\PassOptionsToClass{a4paper}{article}
\AtEndOfClass{\RequirePackage{hypdoc}}
```

Then `source2e.tex` can be compiled by pdfTeX, for example:

```
pdflatex source2e
makeindex -s gind.ist source2e.idx
makeindex -s gglo.ist -o source2e.glo source2e.gls
pdflatex source2e
makeindex -s gind.ist source2e.idx
makeindex -s gglo.ist -o source2e.glo source2e.gls
pdflatex source2e
```

3 Implementation

```
1 {*package}
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{hypdoc}%
4 [2010/02/03 v1.8 Hyper extensions for doc.sty (HO)]%
```

The package identification is done at the top of the `.dtx` file in order to use only one identification string.

For unique command names this package uses `HD@` as prefix

3.1 Options

```
\ifHD@numbered
5 \newif\ifHD@numbered
6 \DeclareOption{numbered}{\HD@numberedtrue}
7 \ProcessOptions*\relax
```

3.2 Package loading

```
8 \RequirePackage{doc}
9 \ifx\numexpr\@undefined
10 \RequirePackage{calc}%
11 \fi
12 \RequirePackage[% hyperindex=false,%
13 pdfusetitle,%
14 colorlinks,%
15 pdfpagelabels,%
16 ]{hyperref}[2002/05/09]%
17 \hypersetup{%
18 plainpages=false,%
19 bookmarksopen,%
20 bookmarksnumbered,%
21 bookmarksopenlevel=0,%
22 pdfstartview={FitBH \hypercalcbp{%
23 \paperheight-\topmargin-1in-\headheight-\headsep
24 }},%
25 }
26 \RequirePackage{thumbpdf}
27 \newcounter{HD@unique}
28 \theHD@unique
29 \renewcommand{\theHD@unique}{%
30 \number\value{HD@unique}%
31 }
32 \g@addto@macro\Hy@UseMaketitleInfos{%
33 \@ifundefined{fileinfo}{}{%
34 \ifx\@pdfsubject\@empty
35 \hypersetup{pdfsubject={\fileinfo}}%
```

```

36     \fi
37   }%
38 }

39 \pdfstringdefDisableCommands{%
40   \let\thanks\@gobble
41   \let\footnote\@gobble
42   \def\cs#1{\textbackslash #1}%
43   \let\normalfont\@empty
44   \let\scshape\@empty
45   \def\and{and }%
46 }

```

3.2.1 Patch for bug latex/4096

```

47 \begingroup\expandafter\expandafter\expandafter\endgroup
48 \expandafter\ifx\csname mod@math@codes\endcsname\relax
49 \else
50   \def\HD@ModFix#1{%
51     \mathcode`#1='#1\relax
52   }%
53   \g@addto@macro\mod@math@codes{%
54     \HD@ModFix\-%
55     \HD@ModFix\+%
56     \HD@ModFix\:%
57     \HD@ModFix\=%
58     \HD@ModFix\*%
59   }%
60 \fi

```

3.3 Bookmarks

```

\HD@sectionpatch
61 \def\HD@sectionpatch{%
62   \ifHD@numbered
63     \HD@@sectionpatch{section}%
64     \HD@@sectionpatch{chapter}%
65   \else
66     \let\Hy@writebookmark\HD@disable@writebookmark
67   \fi
68 }

\HD@@sectionpatch
69 \def\HD@@sectionpatch#1{%
70   \expandafter\let\csname HDorg@@#1\expandafter\endcsname
71   \csname #1\endcsname
72   \cnamedef{#1}{%
73     \c@ifstar{\c@nameuse{HDorg@@#1}}{\c@nameuse{HDorg@@#1}}%
74   }%
75 }

\HD@disable@writebookmark
76 \def\HD@disable@writebookmark#1#2#3#4#5{}

\HD@guesstoclevel A wild guessing of the toplevel. There is the hope, that the macro #1 starts with
a sectioning command.
77 \def\HD@guesstoclevel#1{%
78   \expandafter\HD@@guesstoclevel#1\section\HD@end
79 }

\HD@@guesstoclevel
80 \def\HD@@guesstoclevel#1#2\HD@end{%

```

```

81  \@ifundefined{toclevel@\expandafter\@gobble\string#1\@empty}{%
82    1%
83  }{%
84    \nameuse{toclevel@\expandafter\@gobble\string#1\@empty}%
85  }%
86 }

```

3.4 \tableofcontents

```
\HDorg@tableofcontents
87 \let\HDorg@tableofcontents\tableofcontents

\tableofcontents As first section the table of contents shouldn't go into the toc itself. Also a number
looks too funny then. Just a bookmark is enough in this case.
88 \def\tableofcontents{%
89   \begingroup
90     \@ifundefined{c@section}{%
91       \def\c@section{0}%
92     }{%
93       \expandafter\endgroup
94       \ifcase\c@section
95         \stepcounter{HD@unique}%
96         \pdfbookmark[\HD@guesstoclevel{\HDorg@tableofcontents}]{%
97           \contentsname}{toc\theHD@unique}%
98         \HDorg@tableofcontents
99     \else
100       \ifHD@numbered
101     \else
102       \stepcounter{HD@unique}%
103       \pdfbookmark[\HD@guesstoclevel{\HDorg@tableofcontents}]{%
104         \contentsname}{toc\theHD@unique}%
105     \fi
106     \begingroup
107       \HD@sectionpatch
108       \HDorg@tableofcontents
109     \endgroup
110   \fi
111 }
```

3.5 \listoffigures

```
\HDorg@listoffigures
112 \let\HDorg@listoffigures\listoffigures

\listoffigures
113 \def\listoffigures{%
114   \ifHD@numbered
115   \else
116     \stepcounter{HD@unique}%
117     \pdfbookmark[\HD@guesstoclevel{\HDorg@listoffigures}]{%
118       \contentsname}{toc\theHD@unique}%
119   \fi
120   \begingroup
121     \HD@sectionpatch
122     \HDorg@listoffigures
123   \endgroup
124 }
```

3.6 \listoftables

```
\HDorg@listoftables
125 \let\HDorg@listoftables\listoftables

\listoftables
126 \def\listoftables{%
127   \ifHD@numbered
128   \else
129     \stepcounter{HD@unique}%
130     \pdfbookmark[\HD@guesstoclevel{\HDorg@listoftables}]%
131       {\contentsname{toc\theHD@unique}}%
132   \fi
133   \begingroup
134     \HD@sectionpatch
135     \HDorg@listoftables
136   \endgroup
137 }
```

3.7 \thebibliography

```
\HDorg@thebibliography
138 \let\HDorg@thebibliography\thebibliography

\thebibliography
139 \def\thebibliography{%
140   \ifHD@numbered
141   \else
142     \stepcounter{HD@unique}%
143     \pdfbookmark[\HD@guesstoclevel{\HDorg@thebibliography}]%
144       {\@ifundefined{chapter}{\refname}{\bibname}}{\bib\theHD@unique}}%
145   \fi
146   \HD@sectionpatch
147   \HDorg@thebibliography
148 }
```

3.8 \theindex

```
\HDorg@theindex
149 \let\HDorg@theindex\theindex

\theindex
150 \def\theindex{%
151   \let\HDorg@index@prologue\index@prologue
152   \let\HDorg@writebookmark\Hy@writebookmark
153   \HD@sectionpatch
154   \g@addto@macro\IndexParms{%
155     \ifHD@numbered
156     \else
157       \let\Hy@writebookmark\HDorg@writebookmark
158     \fi
159   \let\bfseries\HD@bfseries
160 }%
161 \edef\HD@toclevel@index{\HD@guesstoclevel{\index@prologue}}%
162 \begingroup
163   \count@=\HD@toclevel@index\relax
164   \advance\count@ by 1 %
165   \xdef\HD@toclevel@subindex{\the\count@}%
166 \endgroup
167 \def\index@prologue{%
168   \ifHD@numbered
```

```

169     \else
170         \begingroup
171             \stepcounter{HD@unique}%
172             \let\Hy@writebookmark\HDorg@writebookmark
173             \pdfbookmark[\HD@toclevel@index]%
174                 {\indexname}{index\theHD@unique}%
175         \endgroup
176     \fi
177     \HDorg@index@prologue
178 }
179 \HDorg@theindex
180 }

\HDorg@bfseries
181 \let\HDorg@bfseries\bfseries

\HD@bfseries
182 \def\HD@bfseries{\futurelet\HD@hfil\HD@@bfseries}%

\HD@@bfseries
183 \def\HD@@bfseries{%
184     \HDorg@bfseries
185     \ifx\HD@hfil\hfil
186         \expandafter\HD@@bfseries
187     \fi
188 }

\HD@@@bfseries
189 \def\HD@@@bfseries\hfil#1\hfil{%
190     \ifx\#1\\%
191     \else
192         \raisebox{\baselineskip}[0pt]{%
193             \kern-\HD@margin\relax
194             \pdfbookmark[\HD@toclevel@subindex]{#1}{\HD.#1}%
195             \kern\HD@margin\relax
196         }%
197     \fi
198     \hfil#1\hfil
199 }%

\HD@margin
200 \def\HD@margin{1mm}

```

3.9 \theglossary

```

\HDorg@theglossary
201 \let\HDorg@theglossary\theglossary

\theglossary
202 \def\theglossary{%
203     \let\HDorg@glossary@prologue\glossary@prologue
204     \let\HDorg@writebookmark\Hy@writebookmark
205     \HD@sectionpatch
206     \def\glossary@prologue{%
207         \ifHD@numbered
208         \else
209             \begingroup
210                 \let\Hy@writebookmark\HDorg@writebookmark
211                 \stepcounter{HD@unique}%
212                 \pdfbookmark[\HD@guesstoclevel{\HDorg@glossary@prologue}]%

```

```

213      {\glossaryname}{glossary\theHD@unique}%
214      \endgroup
215      \fi
216      \HDorg@glossary@prologue
217 }%
218 \HDorg@theglossary
219 }

\glossaryname
220 \providecommand*\glossaryname{Change History}



### 3.10 Index


221 \newcounter{HD@hypercount}
\HD@helplength
222 \newlength{\HD@helplength}

\ifHD@savedest
223 \newif\ifHD@savedest
224 \HD@savedesttrue
225 \AtBeginDocument{%
226   \HD@savedest@init
227 }
228 \RequirePackage{rerunfilecheck}[2009/12/10]

\HD@savedest@init
229 \begingroup
230   \catcode`^\^M=\active
231 \firstofone{\endgroup
232   \def\HD@savedest@init{%
233     \ifHD@savedest
234       \let\HDorg@tilde^%
235       \let`\HD@savedest@entry
236       \edef\HDorg@catcodeM{\the\catcode`^\^M}%
237       \catcode`^\^M=\active
238       \def^\^M{}%
239       \InputIfFileExists{\jobname.hd}{}{%
240         \let`\HDorg@tilde
241         \catcode`^\^M=\HDorg@catcodeM\relax
242         \newwrite\HD@savedest@out
243         \RerunFileCheck{\jobname.hd}%
244           \immediate\closeout\HD@savedest@out
245         }{}%
246         \immediate\openout\HD@savedest@out=\jobname.hd\relax
247     \else
248       \let\HD@savedest@add\@gobble
249     \fi
250   }%
}

\HD@savedest@entry
251 \def\HD@savedest@entry#1^\^M{%
252   \namedef{HD.#1}{}%
253 }%
254 }

\HD@savedest@add
255 \def\HD@savedest@add#1{%
256   \immediate\write\HD@savedest@out{\string^#1}%
257 }

```

```

\ifHD@targetraise
258 \newif\ifHD@targetraise
259 \HD@targetraisetrue

\HD@target
260 \def\HD@target{%
261   \ifHD@targetraise
262     \ifhmode
263       \settoheight{\HD@helplength}{[H]}%
264       \addtolength{\HD@helplength}{0.4ex}%
265       \raisebox{\HD@helplength}{%
266         \HD@maketarget
267       }%
268     \else
269       \HD@maketarget
270     \fi
271   \else
272     \HD@maketarget
273   \fi
274 }

\HD@maketarget
275 \def\HD@maketarget{%
276   \stepcounter{HD@hypercount}%
277   \def\HD@next{%
278     \llap{\hypertarget{HD.\the\c@HD@hypercount}{}},}%
279   }%
280   \ifHD@savedest
281     \expandafter\ifx\csname HD.\the\c@HD@hypercount\endcsname\empty
282   \else
283     \let\HD@next\relax
284   \fi
285 \fi
286 \HD@next
287 }

\CodeIndex
288 \g@addto@macro\CodeIndex{%
289   \let\special@index\HD@codeindex@wrindex
290 }

\PageIndex
291 \g@addto@macro\PageIndex{%
292   \let\special@index\HD@page@wrindex
293 }

\HD@codeindex@wrindex
294 \def\HD@codeindex@wrindex#1{%
295   \begingroup
296   \let\HDorg@encapchar\encapchar
297   \def\encapchar##1\encapchar##2\@nil{%
298     \HDorg@encapchar
299     \hdclindex{\the\c@HD@hypercount}##1}%
300   }%
301   \codeindex@wrindex{%
302     #1\encapchar\encapchar\@nil
303   }%
304 \endgroup
305 }

```

```

\HD@page@wrindex
306 \def\HD@page@wrindex#1{%
307   \begingroup
308     \let\HDorg@encapchar\encapchar
309     \def\encapchar##1\encapchar##2\@nil{%
310       \HDorg@encapchar
311       hdpindex{##1}%
312     }%
313     \HDorg@index{#1\encapchar\encapchar\@nil}%
314   \endgroup
315 }

\hdclindex
316 \def\hdclindex#1#2#3{%
317   \csname\ifx\#2\relax\else#2\fi\endcsname{%
318     \hyperlink{HD.#1}{#3}%
319     \HD@savedest@add{#1}%
320   }%
321 }

\hdpindex
322 \def\hdpindex#1#2{%
323   \csname\ifx\#1\relax\else#1\fi\endcsname{%
324     \hyperpage{#2}%
325   }%
326 }

```

3.11 \PrintDescribeMacro

```

\HDorg@PrintDescribeMacro
327 \let\HDorg@PrintDescribeMacro\PrintDescribeMacro

\PrintDescribeMacro
328 \renewcommand\PrintDescribeMacro[1]{%
329   \begingroup
330     \let\HDorg@MacroFont\MacroFont
331     \def\MacroFont{%
332       \HD@target
333       \HDorg@MacroFont
334     }%
335     \HDorg@PrintDescribeMacro{#1}%
336   \endgroup
337 }

```

3.12 \PrintMacroName

```

\HDorg@PrintMacroName
338 \let\HDorg@PrintMacroName\PrintMacroName

\PrintMacroName
339 \renewcommand\PrintMacroName[1]{%
340   \begingroup
341     \let\HDorg@MacroFont\MacroFont
342     \def\MacroFont{%
343       \HD@target
344       \HDorg@MacroFont
345     }%
346     \HDorg@PrintMacroName{#1}%
347   \endgroup
348 }

```

3.13 \theCodelineNo

```
\HDorg@theCodelineNo
349 \let\HDorg@theCodelineNo\theCodelineNo

\theCodelineNo
350 \renewcommand*\theCodelineNo{%
351   \settowidth{\HD@helplength}{\HDorg@theCodelineNo\ }%
352   \ifdim\HD@helplength<\MacroIndent
353     \addtolength{\HD@helplength}{-\MacroIndent}%
354     \llap{%
355       \begingroup\HD@target\endgroup
356       \hspace*{-\HD@helplength}%
357     }%
358   \else
359     \HD@target
360   \fi
361 \HDorg@theCodelineNo
362 }

\HDorg@index
363 \AtBeginDocument{%
364   \let\HDorg@index\index
365 }
```

3.14 \SpecialUsageIndex

```
\HDorg@SpecialUsageIndex
366 \let\HDorg@SpecialUsageIndex\SpecialUsageIndex
367 \renewcommand*\SpecialUsageIndex[1]{%
368   \@bsphack
369   \begingroup
370     \HD@target
371     \let\index\HDorg@index
372     \let\HDorg@encapchar\encapchar
373     \edef\encapchar usage{%
374       \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}}%
375     }%
376     \HDorg@SpecialUsageIndex{#1}%
377   \endgroup
378   \@esphack
379 }
```

3.15 \autoindex

```
380 \begingroup\expandafter\expandafter\expandafter\endgroup
381 \expandafter\ifx\csname autoindex\endcsname\relax
382 \else
```

```
\HDorg@autoindex
383   \let\HDorg@autoindex\autoindex

\autoindex
384   \renewcommand*\autoindex[1]{%
385     \@bsphack
386     \begingroup
387       \HD@target
388       \let\index\HDorg@index
389       \let\HDorg@encapchar\encapchar
390       \edef\encapchar usage{%
391         \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}}%
```

```

392      }%
393      \HDorg@autoindex{#1}%
394      \endgroup
395      \esphack
396  }%
397 \fi

```

3.16 \SpecialEnvIndex

```
\HDorg@SpecialEnvIndex
398 \let\HDorg@SpecialEnvIndex\SpecialEnvIndex
```

```
\SpecialEnvIndex
```

```

399 \renewcommand*\SpecialEnvIndex[1]{%
400   \bsphack
401   \begingroup
402     \HD@target
403     \let\HDorg@encapchar\encapchar
404     \edef\encapchar usage{%
405       \HDorg@encapchar hdclindex{\the\c@HD@hypercount}{usage}%
406     }%
407     \HDorg@SpecialEnvIndex{#1}%
408   \endgroup
409   \esphack
410 }

```

3.17 \SortIndex

```
\HDorg@SortIndex
```

```
411 \let\HDorg@SortIndex\SortIndex
```

```
\SortIndex
```

```

412 \renewcommand*\SortIndex[2]{%
413   \bsphack
414   \begingroup
415     \let\index\HD@page@wrindex
416     \HDorg@SortIndex{#1}{#2}%
417   \endgroup
418   \esphack
419 }

```

3.18 \@wrglossary

```
\HDorg@wrglossary
```

```
420 \let\HDorg@wrglossary\@wrglossary
```

```
\@wrglossary
```

```

421 \def\@wrglossary#1{%
422   \let\HDorg@encapchar\encapchar
423   \def\encapchar##1\encapchar##2\@nil{%
424     \HDorg@encapchar
425     hdpindex{##1}%
426   }%
427   \HDorg@wrglossary{#1\encapchar\encapchar\@nil}%
428 }

```

3.19 \MacroIndent

```
\MacroIndent automatically calculated.  
429 \AtEndDocument{  
430   \if@files  
431     \immediate\write\@auxout{  
432       \noexpand\HD@SetMacroIndent{\number\value{CodelineNo}}%  
433     }%  
434   \fi  
435 }  
  
\HD@SetMacroIndent  
436 \def\HD@SetMacroIndent#1{  
437   \begingroup  
438     \value{CodelineNo}=#1\relax  
439     \settowidth{\MacroIndent}{\HDorg@theCodelineNo\ }%  
440     \global\MacroIndent\MacroIndent  
441   \endgroup  
442 }  
  
443 </package>
```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/hypdoc.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/hypdoc.pdf Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

CTAN:install/macros/latex/contrib/oberdiek.tds.zip

TDS refers to the standard “A Directory Structure for T_EX Files” (CTAN:tds/tds.pdf). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl  
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex hypdoc.dtx
```

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
hypdoc.sty → tex/latex/oberdiek/hypdoc.sty  
hypdoc.pdf → doc/latex/oberdiek/hypdoc.pdf  
hypdoc.dtx → source/latex/oberdiek/hypdoc.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TeX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk hypdoc.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-`TeX`: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
\latex \let\install=y\input{hypdoc.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex hypdoc.dtx  
makeindex -s gind.ist hypdoc.idx  
pdflatex hypdoc.dtx  
makeindex -s gind.ist hypdoc.idx  
pdflatex hypdoc.dtx
```

5 History

[2002/05/10 v1.0]

- First standalone version.

[2006/02/20 v1.1]

- Option numbered added.
- `\HD@savedest@init` fixed (empty .hd file triggered first page with fl ligature).
- Bookmarks for `\listoffigures` and `\listoftables`.
- Documentation: features and usage added.
- LPPL 1.3.

[2006/04/27 v1.2]

- `\HD@target` fixed (`multicol.dtx`).

[2006/06/01 v1.3]

- Support for package `amsdtx`'s `\autoindex` added.

[2006/06/02 v1.4]

- Bookmark fixed if there are several table of contents, bibliographies, glossaries, ...

[2007/04/11 v1.5]

- Line ends sanitized.

[2007/11/12 v1.6]

- Bug fix in `\listoffigures` (Axel Sommerfeldt).
- Markup added in implementation section.

[2009/12/10 v1.7]

- Use of package `rerunfilecheck`.

[2010/02/03 v1.8]

- Fix for bug latex/4096 added.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
<code>*</code>	58	<code>\@firstofone</code>
<code>\+</code>	55	<code>\@gobble</code> 40, 41, 81, 84, 248 <code>\@ifstar</code> 73
<code>\,</code>	278	<code>\@ifundefined</code> 33, 81, 90, 144
<code>\-</code>	54	<code>\@namedef</code> 72, 252
<code>\:</code>	56	<code>\@nameuse</code> 73, 84
<code>\=</code>	57	<code>\@nil</code> 297, 302, 309, 313, 423, 427
<code>\@auxout</code>	431	<code>\@pdfsubject</code> 34
<code>\@bsphack</code>	368, 385, 400, 413	<code>\@undefined</code> 9
<code>\@empty</code>	34, 43, 44, 81, 84, 281	<code>\@wrglossary</code> 420, 421
<code>\@esphack</code>	378, 395, 409, 418	<code>\`</code> 190, 317, 323

\`	230, 236, 237, 241	\HD@hfil	182, 185
_	351, 439	\HD@maketarget	266, 269, 272, 275
A			
\active	230, 237	\HD@margin	193, 195, 200
\addtolength	264, 353	\HD@ModFix	50, 54, 55, 56, 57, 58
\advance	164	\HD@next	277, 283, 286
\and	45	\HD@numberedtrue	6
\AtBeginDocument	225, 363	\HD@page@wrindex	292, 306, 415
\AtEndDocument	429	\HD@savedest@add	248, 255, 319
\autoindex	383, 384	\HD@savedest@entry	235, 251
B			
\baselineskip	192	\HD@savedest@init	226, 229
\bfseries	159, 181	\HD@savedest@out	242, 244, 246, 256
\bibname	144	\HD@savedesttrue	224
C			
\c@HD@hypercount	278, 281, 299, 374, 391, 405	\HD@sectionpatch 61, 107, 121, 134, 146, 153, 205
\c@section	91, 94	\HD@SetMacroIndent	432, 436
\catcode	230, 236, 237, 241	\HD@target	260,
\closeout	244	332, 343, 355, 359, 370, 387, 402	
\codeline@wrindex	301	\HD@targetraisettrue	259
\CodelineIndex	288	\HD@toclevel@index	161, 163, 173
\contentsname	97, 104, 118, 131	\HD@toclevel@subindex	165, 194
\count@	163, 164, 165	\hdclindex	316
\cs	42	\HDorg@autoindex	383, 393
\csname	48, 70, 71, 281, 317, 323, 381	\HDorg@bfseries	181, 184
D			
\DeclareOption	6	\HDorg@catcodeM	236, 241
E			
\encapchar	296, 297, 302, 308, 309, 313, 372, 373, 389, 390, 403, 404, 422, 423, 427	\HDorg@encapchar 296, 298, 308, 310, 372, 374, 389, 391, 403, 405, 422, 424
\endcsname	48, 70, 71, 281, 317, 323, 381	\HDorg@glossary@prologue	203, 212, 216
F			
\fileinfo	35	\HDorg@index	313, 363, 371, 388
\footnote	41	\HDorg@index@prologue	151, 177
\futurelet	182	\HDorg@listoffigures	112, 117, 122
G			
\g@addto@macro	32, 53, 154, 288, 291	\HDorg@listoftables	125, 130, 135
\glossary@prologue	203, 206	\HDorg@MacroFont	330, 333, 341, 344
\glossaryname	213, 220	\HDorg@PrintDescribeMacro	327, 335
H			
\HD@@bfseries	186, 189	\HDorg@PrintMacroName	338, 346
\HD@@bfseries	182, 183	\HDorg@SortIndex	411, 416
\HD@@guesstoclevel	78, 80	\HDorg@SpecialEnvIndex	398, 407
\HD@@sectionpatch	63, 64, 69	\HDorg@SpecialUsageIndex	366
\HD@bfseries	159, 182	\HDorg@tableofcontents 87, 96, 98, 103, 108
\HD@codeline@wrindex	289, 294	\HDorg@thebibliography	138, 143, 147
\HD@disable@writebookmark	66, 76	\HDorg@theCodelineNo	349, 351, 361, 439
\HD@end	78, 80	\HDorg@theglossary	201, 218
\HD@guesstoclevel	77, 96, 103, 117, 130, 143, 161, 212	\HDorg@theindex	149, 179
\HD@helplength	222, 263, 264, 265, 351, 352, 353, 356	\HDorg@tilde	234, 240
		\HDorg@wrglossary	420, 427
		\HDorg@writebookmark 152, 157, 172, 204, 210
		\hdpindex	322
		\headheight	24
		\headsep	24
		\hfil	185, 189, 198
		\hspace	356
		\Hy@UseMaketitleInfos	32
		\Hy@writebookmark 66, 152, 157, 172, 204, 210
		\hypercalcbp	23
		\hyperlink	318
		\hyperpage	324
		\hypersetup	18, 35
		\hypertarget	278

	I	
\if@files w	430	\paperheight 24
\ifcase	94	\pdfbookmark 96, 103, 117, 130, 143, 173, 194, 212
\ifdim	352	\pdfstringdefDisableCommands 39
\ifHD@numbered	5, 62, 100, 114, 127, 140, 155, 168, 207	\PrintDescribeMacro 327, 328
\ifHD@savedest	223, 233, 280	\PrintMacroName 338, 339
\ifHD@targetraise	258, 261	\ProcessOptions 7
\ifhmode	262	\providecommand 220
\ifx	9, 34, 48, 185, 190, 281, 317, 323, 381	\ProvidesPackage 3
\immediate	244, 246, 256, 431	
\index	364, 371, 388, 415	R
\index@prologue	151, 161, 167	\raisebox 192, 265
\indexname	174	\refname 144
\IndexParms	154	\renewcommand 29, 328, 339, 350, 367, 384, 399, 412
\InputIfFileExists	239	\RequirePackage 8, 10, 12, 27, 228
		\RerunFileCheck 243
	J	
\jobname	239, 243, 246	
	K	
\kern	193, 195	
	L	
\listoffigures	112, 113	
\listoftables	125, 126	
\llap	278, 354	
	M	
\MacroFont	330, 331, 341, 342	
\MacroIndent	352, 353, 439, 440	
\mathcode	51	
\mod@math@codes	53	
	N	
\NeedsTeXFormat	2	
\newcounter	28, 221	
\newif	5, 223, 258	
\newlength	222	
\newwrite	242	
\normalfont	43	
\number	30, 432	
\numexpr	9	
	O	
\openout	246	
	P	
\PageIndex	291	
	S	
\scshape	44	
\section	78	
\settoheight	263	
\settowidth	351, 439	
\SortIndex	411, 412	
\special@index	289, 292	
\SpecialEnvIndex	398, 399	
\SpecialUsageIndex	366, 367	
\stepcounter	95, 102, 116, 129, 142, 171, 211, 276	
	T	
\tableofcontents	87, 88	
\textbackslash	42	
\thanks	40	
\the	165, 236, 278, 281, 299, 374, 391, 405	
\thebibliography	138, 139	
\theCodelineNo	349, 350	
\theglossary	201, 202	
\theHD@unique	29, 97, 104, 118, 131, 144, 174, 213	
\theindex	149, 150	
\topmargin	24	
	V	
\value	30, 432, 438	
	W	
\write	256, 431	